



Art.no. 4200

Art.no. 4201

Art.no. 4200

High pressure grease control gun, steel body, inlet connection 1/4" BSP (M), outlet connection M 10x1.
Working pressure up to 800 bar.

Art.no. 4201

High pressure grease control gun art.no. 4200, but additionally equipped with a trigger guard.



Art.no. 4206

Art.no. 4205

Art.no. 4205

High pressure grease control gun with 300 mm – steel braid rubber outlet hose ø ext. 10 mm and 4 - jaws - hydraulic coupler.
Working pressure up to 800 bar.

Art.no. 4206

High pressure grease control gun art.no. 4205, but additionally equipped with a trigger guard.



Art.no. 4207

Art.no. 4208

Art.no. 4208

High pressure grease control gun with rigid outlet pipe and 4 – jaws – hydraulic coupler.
Working pressure up to 800 bar.

Art.no. 4207

High pressure grease control gun art.no. 4208, but additionally equipped with a trigger guard.



Art.no. 4209

Art.no. 4204

Art.no. 4209

High delivery grease control gun for the transfer of grease, with rigid outlet, ø 20 mm.
Working pressure up to 200 bar, burst pressure 350 bar.

Art.no. 4204

Grease control gun for the transfer of grease, with rigid outlet, ø 16 mm. Working pressure up to 180 bar, burst pressure 320 bar.



Art.no. 4228

Art.no. 4221

Art.no. 4221

High pressure rotating "Z" – swivel, connections 1/4" BSP (M – F). For the installation between hose and control gun. Allows a complete 360° - rotation on the 3 axes, also under pressure.

Art.no. 4228

Straight high pressure rotating swivel, connections 1/4" BSP (M – F). For the installation between hose and control gun. Allows a complete 360° - rotation on the 1 axe, also under pressure.