

Art.no. **6933**

Wall-mounted petrol transfer kit, composed of 1:1 - pneumatic piston pump, pressure regulator and air filter with moisture separator, wall bracket, suction hose with foot valve, 3 m – rubber supply hose 3/4" with static wire, automatic shut-off dispensing nozzle with inlet swivel. On demand the pump can be supplied with an earth cable to enable an electrostatic discharge.

It is constructed in accordance with directive ATEX 2014/34/EU.



Art.no.	Compressed air supply	Air consumption	Max outlet pressure	Max delivery	Connection threads	Weight
<b>6933</b>	1 – 4 bar	120 l/min	4 bar	25 l/min	3/4" BSP (F)	15 kg

Art.no. **6934**

Petrol transfer kit, composed of 1:1 - pneumatic rotary vane pump, pressure regulator and air filter with moisture separator, suction tube of 950 mm length with non-return valve, bung adapter, 3 m – rubber hose 3/4" with static wire, automatic shut-off dispensing nozzle with inlet swivel. On demand the pump can be supplied with an earth cable to enable an electrostatic discharge.

It is constructed in accordance with directive ATEX 2014/34/EU.



Art.no.	Compressed air supply	Air consumption	Max outlet pressure	Max delivery	Connection threads	Weight
<b>6934</b>	4 bar	160 l/min	4 bar	35 l/min	3/4" BSP (F)	12 Kg

Art.no. **6935**

Petrol transfer kit, composed of electric, selfpriming 12 VDC – rotary vane pump with painted body in cast iron with anticorrosive coating, anti-noise filter (electromagnetic compatibility EMC), thermal protection, non-return valve, pressure relief valve, built-in bypass valve, 2 m – cable with alligator clamps for battery connection, nozzle holster with lock and ON-/OFF-lever, telescopic suction tube in galvanized steel, 3 m – rubber hose 3/4" with static wire, manual aluminium nozzle with inlet swivel (on demand also automatic shut-off dispensing nozzle available!) and in-line filter with 30 microns – cartridge for the absorption of water that is eventually present in the storage tank.

The pump is constructed in accordance with directive ATEX 2014/34/EU – IECEx (group II – category 2 – G Ex d IIA T4 Gb).



Art.no. **6937**

Dispensing unit as art. no. 6935 but with pump at 230 VAC.



Art. no.	Voltage	Power	Current drain	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6935</b>	12 VDC	250 W	1 A	50 l/min	1" BSP (F)	10 Kg	400x500x460
<b>6937</b>	230 VAC						

