

Art.no. **6728**

Automatic shut-off dispensing nozzle for petrol, with rubber protection.



Mod.	Flow range	Connection threads	Diameter outlet spout	Weight
6728	1 - 60 l/min	3/4" BSP (F)	20 mm	1.2 kg

Art.no. **2867**

Mechanical nutating – disk flow meter for petrol, kerosene and diesel, with 3 – digits partial meter (max. 999 l; resettable to zero) and 8 – digits totalizer (non resettable). The meter can easily be calibrated and it can also be used for gravity applications. The upper part can be rotated so that different flow directions are possible.

The flow meter is constructed in accordance with directive ATEX 2014/34/EU – IECEx (group II – category 2 – G Ex d IIA T4 Gb).



Art. no.	Flow range	Max working pressure	Burst pressure	Accuracy*	Resolution	Connection threads	Weight
2867	20 – 120 l/min	3.5 bar	28 bar	+/- 1%	0.01 l	1" BSP (F)	0.6 kg

Art.no. **2868**

Mechanical nutating – disk flow meter for petrol, kerosene and diesel, with 4 – digits partial meter (max. 9999 l; resettable to zero) and 8 – digits totalizer (non resettable). The meter can easily be calibrated and it can also be used for gravity applications. The upper part can be rotated so that different flow directions are possible.

The flow meter is constructed in accordance with directive ATEX 2014/34/EU – IECEx (group II – category 2 – G Ex d IIA T4 Gb).



Art. no.	Flow range	Max working pressure	Burst pressure	Accuracy*	Resolution	Connection threads	Weight
2868	20 – 120 l/min	3.5 bar	28 bar	+/- 1%	0.01 l	1" BSP (F)	0.6 kg

*Accuracy in % of flow range after calibration