




Portable diesel storage tank in polyethylene (wall thickness 5 mm), suitable for the transport in trucks or pick-ups, with ADR – approval (according to ADR 1.1.3.1.c), including refill tube, air vent valve, level gauge, forklift pockets and handles for transport (empty), equipped with electric, selfpriming vane pump 12 VDC (on demand also 24 VDC) with a delivery of 40 l/min, ON-/OFF-switch, automatic shut-off dispensing nozzle, 4 m – rubber delivery hose \varnothing 3/4" and 2 m – cable with alligator clamps for battery connection. Includes a lockable plastic cover.

Optional: electronic diesel flow meter (art. no. 2823).

Art. no.	Capacity	Weight	Dimensions (LxWxH) (mm)
8223/220	220 l	28 kg	800x600x700
8223/430	430 l	58 kg	1200x800x750
8223/600	600 l	62 kg	1200x800x1020




Portable petrol storage tank in high density polyethylene, electrically conductive, to enable an electrostatic discharge, suitable for the transport in trucks or pick-ups, with ADR – approval (according to ADR 6.5.4.4.1 b and 6.5.4.4.2 b), including refill tube, air vent valve, level gauge, forklift pockets and handles for transport (empty), equipped with electric, selfpriming rotary vane pump 12 VDC (on demand also 24 VDC) with a delivery of 40 l/min. (constructed in accordance with directive ATEX, 4 m – cable with alligator clamps for battery connection, 4 m – statically conductive rubber supply hose, automatic shut-off dispensing nozzle and nozzle holder. Includes a lockable plastic cover

On demand also available with manual dispensing pump.



Art. no.	Capacity	Weight	Dimensions (LxWxH) (mm)
8224/120	120 l	26 kg	800x600x470
8224/190	190 l	38 kg	800x600x610



Petrol



Portable storage tank for AdBlue®/DEF/AUS32 in high density polyethylene, suitable for the transport in trucks or pick-ups, including refill tube, air vent valve, level gauge, forklift pockets and handles for transport (empty), equipped with electric, selfpriming diaphragm pump 12 VDC (on demand also 24 VDC) with a delivery of 25 l/min, ON-/OFF-switch, automatic shut-off dispensing nozzle, 4 m – delivery hose in EPDM, and 4 m – cable with alligator clamps for battery connection. Includes a lockable plastic cover.

Optional: electronic flow meter, suitable for AdBlue®/DEF/AUS32 (art. no. 2822).

Art. no.	Capacity	Weight	Dimensions (LxWxH) (mm)
8225/125	125 l	20 kg	800x600x450
8225/210	210 l	21 kg	790x600x690
8225/440	440 l	37 kg	1180x800x710
8225/600	600 l	52 kg	1160x800x1020

