

Pneumatic pumps, standard series, with cylinder in stainless steel AISI 304 and EPDM gaskets for the supply of fluids with particular chemical characteristics. It is recommended to check the compatibility of the fluid with the materials of the wetted pump components before use.



Art.no **1045**



Art.no **1071**



Art.no **1072**



Art.no **1049**



Art.no **1050**

Stainless Steel

| Art. no. | 1045 | 1049 | 1071 | 1072 | 1050 |
|---|--------------------------------|--------------|-------------------|--------------|--------------|
| Compressed air supply | Compressed air Min 2 Max 8 bar | | | | |
| Compression ratio | 1:1 | 3:1 | 1:1 | 1:1 | 3:1 |
| Outlet pressure | 8 bar | 24 bar | 8 bar | 8 bar | 24 bar |
| Delivery | 35 l/min | 15 l/min | 35 l/min | 35 l/min | 15 l/min |
| Connection compressed air | 1/4" BSP (F) | | | | |
| Connection lubricant outlet | 3/4" BSP (F) | 1/2" BSP (M) | 3/4" BSP (F) | 3/4" BSP (F) | 1/2" BSP (M) |
| Max air consumption with 8 bar pressure | 210 l/min | | | | |
| Length suction tube | 260 mm | 260 mm | 1000 mm / 1300 mm | 1000 mm | 1000 mm |
| Gaskets | EPDM | | | | |
| Weight | 5 Kg | 4 Kg | 5.2 Kg | 7 Kg | 4.2 Kg |