

Oil

**Oil Hflow**

new

new



Art.no. **2434**



Art.no. **2435**

Art.no. **2434**

Electronic oval gears high delivery flow meter for oil, **series Oil HFlow**, with control dispensing nozzle Ø 3/4", trigger guard, cartridge filter, rigid outlet, automatic anti-drip nozzle and 3/4" BSP (M) inlet swivel.

This high volume series allows to accelerate the oil supplies by the use of a flow meter that guarantees high accuracy measurement even at high flow rates.

Art.no. **2706**

Rubber protection guard, giant type, suitable for flow meters of high delivery series "Oil HFlow". Provides a good protection against any shocks.



Art.no. **2435**

Electronic oval gears high delivery flow meter for oil, **series Oil HFlow**, with control dispensing nozzle Ø 3/4", trigger guard, cartridge filter, flexible rubber outlet Ø 3/4", automatic anti-drip nozzle and 3/4" BSP (M) inlet swivel.

Art.no.	<b>2434</b>	<b>2435</b>
Connections	3/4" BSP (M)	
Flow range	10 - 100 l/min	
Operating temperature range	+ 10°C / + 50°C	
Max working pressure	70 bar (1015 psi)	
Accuracy	+/- 0.5%	
Total max resettable	9999 l	
Total max non resettable	9999 l	
Weight	3.7 kg	

Not approved for fiscal transactions.