

**Oil Hflow**

Art.no. **2854**

Electronic oval gears high delivery flow meter for oil, **series Oil HFlow**, with control dispensing nozzle Ø 1", trigger guard, cartridge filter, rigid outlet Ø 20 mm, automatic anti-drip nozzle and 1" BSP (M) inlet swivel.

This high volume series allows to accelerate the oil supplies by the use of a flow meter that guarantees high accuracy measurement even at high flow rates.



Art.no. **2854**



Art.no. **2851**



Art.no. **2855**

Art.no. **2851**

Electronic oval gears high delivery flow meter for oil, **series Oil HFlow**, suitable for inline applications, connections 1" BSP (F).

Art.no. **2855**

Electronic oval gears high delivery flow meter for oil, **series Oil HFlow**, with control dispensing nozzle Ø 1", trigger guard, cartridge filter, flexible rubber outlet Ø 1", automatic anti-drip nozzle and 1" BSP (M) inlet swivel.

Art.no.	<b>2851</b>	<b>2854</b>	<b>2855</b>
Connections	1" BSP (F)	1" BSP (M)	
Flow range	20 - 120 l/min	20 - 80 l/min	
Operating temperature range	+ 10°C / + 50°C		
Max working pressure	75 bar (1125 psi)	80 bar (1200 psi)	
Accuracy	+/- 0.5%		
Total max resettable	9999 l		
Total max non resettable	9999 l		
Weight	1.6 kg	3.9 kg	3.9 kg

Not approved for fiscal transactions.