

**Art.no. 2710**

Mechanical oval gears flow meter, with body in aluminium, for oil and antifreeze, with two totalizers.



**Art.no. 2712**

Mechanical oval gears flow meter for oil, with control dispensing nozzle, rigid outlet,  $\varnothing$  12 mm, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M). Composed of art. nos. 2710 and 2185.

Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Total max resettable	Total max non resettable	Weight
<b>2710</b>	1/2" BSP (F)	15 l/min	+10°C / +50°C	50 bar (725 psi)	+ / - 0.5%	999.9 l	999999 l	0.68 Kg
<b>2712</b>	1/2" BSP (M)							1.1 Kg

**Art.no. 2703**

Mechanical, analogical flow meter for oil and antifreeze, with two totalizers, suitable for inline applications.

**Art.no. 2608**

Mechanical, analogical flow meter for oil, with control dispensing nozzle, rigid outlet  $\varnothing$  12 mm, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M). Composed of art. nos. 2703 and 2185.



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Total max resettable	Total max non resettable	Weight
<b>2703</b>	1/2" BSP (F)	15 l/min	+10°C / +50°C	70 bar (1015 psi)	+ / - 0.5%	0-10 l	9999 l	0.86 Kg
<b>2608</b>	1/2" BSP (M)							1.6 Kg

**Art.no. 2508**

Mechanical, analogical preset flow meter for oil, with integrated control dispensing nozzle, trigger guard, rigid outlet  $\varnothing$  12 mm, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M). Preset values 0 – 60 l. This model with integrated control dispensing nozzle, but without preset function is available on demand as well (art. no. 2507).



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Total max resettable	Total max non resettable	Weight
<b>2508</b>	1/2" BSP (M)	15 l/min	+10°C / +50°C	70 bar (1015 psi)	+ / - 0.5%	0-16 l 0-60 l	9999 l	1.6 Kg

**Art.no. 2954**

Electronic oval gears flow meter with pulse transmitter, suitable for oil and antifreeze. Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.



**Art.no. 2716**

Electronic oval gears flow meter with pulse transmitter, body in IXEF. Suitable for the use with water-based fluids and AdBlue® (DEF).

Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight
<b>2954</b>	1/2" BSP (M)	35 l/min	+5°C / +50°C	70 bar (1015 psi)	+ / - 0.5%	78/l	0.6 Kg
<b>2716</b>				30 bar (435 psi)			0.4 Kg

**Art.no. 2853**

Electronic oval gears high delivery flow meter with pulse transmitter, suitable for oil, diesel and antifreeze. Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight
<b>2853</b>	1" BSP (F)	70 l/min	+ 5°C / +50°C	70 bar (1015 psi)	+ / - 0.5%	50/l	1.6 kg