



Art.no. **2980C**

Stationary pneumatic oil dispensing kit for 208 l - drums, consisting of:

- Pneumatic double acting 3:1 - oil pump, art. no. 2020 (see page 41!);
- Plastic bung adapter for the fixation of pumps on drums, art. no. 4340;
- 3 m - rubber hose Ø 1/2", art. no. 28703;
- Oil control dispensing nozzle with 1/2" BSP (M) inlet swivel, rigid outlet and automatic anti-drip nozzle, art. no. 2185;
- Pressure regulator and air filter with moisture separator, art. no. 7180.



Art.no. **2982**

Stationary pneumatic oil dispensing kit with electronic oil flow meter, for 208 l - drums, consisting of:

- Pneumatic double acting 3:1 - oil pump, art. no. 2020 (see page 41!);
- Plastic bung adapter for the fixation of pumps on drums, art. no. 4340;
- 3 m - rubber hose Ø 1/2", art. no. 28703;
- Electronic flow meter for oil, with control dispensing nozzle, rubber protection guard, trigger guard, rigid outlet, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M), art. no. 2426 (see page 64!);
- Pressure regulator and air filter with moisture separator, art. no. 7180.



Art.no. **2987MID**

Stationary pneumatic oil dispensing kit, **approved for fiscal transactions** according to the European Directive 2014/32/EU, better known as **Measurement Instrument Directive MID MI-005**, consisting of:

- Pneumatic double acting 3:1 - oil pump, art. no. 2032 (see page 41!);
- Wall bracket in painted steel, for the fixation of the pump;
- Air separator kit art.no. 2050, patented, approved according to **OIML R117-1** (see page 51!);
- Manometer for outlet pressure control;
- Suction tube in galvanized steel, Ø 40 mm, length 950 mm, with 90° - curved connection 1" BSP (M), with foot valve, at. no. 2204, and bung adapter 2" BSP (M) x 40 mm, art. no. 4340, suitable for the use in 208 l - drums;
- 1.5 m - rubber suction hose 1", connections 1" BSP (F-F), art. no. 2205;
- 3 m - rubber hose Ø 1/2", art. no. 28703;
- Electronic oval gears flow meter for oil, approved for fiscal transactions **according to MID MI-005, Directive 2014/32/EU**, with control dispensing nozzle, rubber protection guard, trigger guard, oil flow control tube with transparent insert, flexible rubber outlet, Ø 1/2", with curved rigid 90° stem, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M), art. no. 2545 (see page 65!).

Art.no. **2987AG/MID**

Stationary, pneumatic oil dispensing kit such as art.no. 2987/MID, but suitable for the use with antifreeze.