


Art.no. **5904**



Stationary parts cleaner in painted steel, with closed circuit of detergent fluid, consisting of cleaning basin with 4 legs and closable and removable cover, hose with shower head, cleaning fluid flowing through the rough brush which permits a continuous flow of the detergent and an accurate cleaning of parts. The system enables a continuous fluid circulation at 0.5 bar pressure by the use of an electric immersion pump.

Note: please use only suitable detergents and degreasing agents for the parts cleaning.

	Voltage	Power	Current drain	Rpm	Protection category
Pump	230 VAC	60 W	0.4 A	2800	IP 54
Art. no.	Max pressure	Total capacity cleaning basin	Usable capacity cleaning basin	Weight	Dimensions (LxWxH) (mm)
5904	0.5 bar	138 l	62 l	53 Kg	500x700x1120




Art.no. **5905**



Stationary parts cleaner in painted steel, with closed circuit of detergent fluid, consisting of cleaning basin with 4 legs and closable and removable cover, hose with shower head, cleaning fluid flowing through the rough brush which permits a continuous flow of the detergent and an accurate cleaning of parts, wooden footboard. The system enables a continuous fluid circulation at 0.5 bar pressure by the use of an electric immersion pump. The switch-on and switch-off of the pump is made through a pedal-operated switch.

Note: please use only suitable detergents and degreasing agents for the parts cleaning.

	Voltage	Power	Current drain	Rpm	Protection category
Pump	230 VAC	60 W	0.4 A	2800	IP 54
Art. no.	Max pressure	Total capacity cleaning basin	Usable capacity cleaning basin	Weight	Dimensions (LxWxH) (mm)
5905	0.5 bar	200 l	90 l	67 Kg	500x1000x1120



Art.no. **5906**



Stationary parts cleaner in painted steel, with closed circuit of detergent fluid, consisting of cleaning basin with 4 legs and closable and removable cover, hose with shower head, cleaning fluid flowing through the rough brush which permits a continuous flow of the detergent and an accurate cleaning of parts. The system enables a continuous fluid circulation by the use of a pneumatic rotary pump in stainless steel (art. no. 1058).

Note: please use only suitable detergents and degreasing agents for the parts cleaning.



Art. no.	Compressed air supply	Max pressure	Total capacity cleaning basin	Usable capacity cleaning basin	Weight	Dimensions (LxWxH) (mm)
5906	1 - 4 bar	4 bar	200 l	90 l	67 Kg	500x1000x1120

