


Art.no. **4400**
Art.no. **4400/4**



Lever action grease gun, suitable for the use with bulk grease or with grease cartridges. With plastic flexible outlet hose \varnothing ext. 8 mm x 300 mm length, M 10x1, and 4 – jaws – hydraulic coupler. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4400	1.2 cm ³ /stroke	300 bar	600 g	56 mm	300 mm	1.70 kg	150x60x480
4400/4		400 bar	400 g	52 mm	240 mm	1.70 kg	110x60x370




Art.no. **4450**
Art.no. **4450/4**



Pneumatic grease gun, suitable for the use with bulk grease or with grease cartridges. With plastic flexible outlet hose \varnothing ext. 8 mm x 300 mm length, M 10x1, and 4 – jaws – hydraulic coupler. It is a single action mechanism (non-continuous grease supply): when activating the trigger, the internal piston moves and supplies grease; when the trigger is released, the piston returns in its initial position. By repeating this procedure the grease can be dispensed. Compressed air pressure: 4 – 8 bar. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4450	1.2 cm ³ /stroke	300 bar	600 g	56 mm	300 mm	2 kg	240x70x550
4450/4		300 bar	400 g	52 mm	240 mm	2 kg	240x70x470



Art.no. **4450/C**




new

Pneumatic grease gun with a continuous grease flow, suitable for the use with bulk grease or with grease cartridges. With rigid outlet pipe 150 mm length, M 10x1, and 4 – jaws – hydraulic coupler.

Compressed air pressure: 2 – 8 bar. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4450/C	0.8 cm ³ /stroke	400 bar	400 g	52 mm	240 mm	2 kg	170x75x400



Art.no. **4408**




new

One-hand-operated grease gun, professional version, suitable for the use with bulk grease or with grease cartridges.

With plastic flexible outlet hose \varnothing ext. 8 mm x 300 mm length, M10x1, and 4 – jaws – hydraulic coupler. The grease dispensing nozzle can be used in a "high volume" or in a "high pressure" mode.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4408	1.1 cm ³ /stroke	200 bar	400 g	52 mm	240 mm	1.6 kg	165x66x400
	0.8 cm ³ /stroke	300 bar					



Art. no. **4405** Cartridge with lithium grease, NLGI 2, with 600 g capacity. Diameter 56 mm, length 300 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According DIN 51502 K 2 K-20. Packaging unit: 15 pcs.

Art. no. **4406** Cartridge with lithium grease, NLGI 2, with 400 g capacity. Diameter 52 mm, length 235 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According DIN 1284. Packaging unit: 15 pcs.