

Art.no. **6123**

Electric, selfpriming gear pump for the supply of AdBlue®; guarantees a constant flow and a low noise level.
Pump body and gears in IXEF.
Protection category IP 55.
Includes ON/OFF – switch and 1.5 m – cable with plug.



Art. no.	Voltage	Current drain	Rpm	Power	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6123	230 VAC 50 Hz	5.3	1360	250 W	2 bar	25 l/min	1/2" BSP (M)	7 kg	240x290x180



Art.no. **6132**

Electric, selfpriming gear pump for the supply of AdBlue®; guarantees a constant flow and a low noise level.
Pump body in stainless steel AISI 304, gears in Kevlar®.
Protection category IP 55.
Includes ON/OFF – switch and 1.5 m – cable with plug and a bypass valve preset on 5 bar pressure.



Art. no.	Voltage	Current drain	Rpm	Power	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6132	230 VAC - 50 Hz	5.3 A	2650	370 W	4 bar	11 l/min	3/8" BSP (F)	7.5 Kg	150x300x190



Art.no. **6157**
Art.no. **6158**

Electric, selfpriming gear pump, with motor in 12 VDC or 24 VDC, for the supply of AdBlue®.
Pump body and gears in IXEF.
Includes ON/OFF-switch and 2.5 m – cable with alligator clamps for battery connection.



Art. no.	Voltage	Current drain	Rpm	Power	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6157	12 VDC	30 A	2800	240 W	2 bar	25 l/min	1/2" BSP (M)	3.6 Kg	260x130x140
6158	24 VDC	15 A							

