

Art.no. **3137P**

Mobile, pneumo-hydraulic cutter unit with max. blades opening of 130 mm. Allows the cutting of vehicle catalyts with extreme speed and high safety.

This unit includes a base with 3 castors, on which is installed a hydraulic lifting device with tray for the height adjustment of the cutter, a 5 l - oil container with 100:1 - pneumatic piston pump, pressure regulator with manometer, moisture separator and lubricator and a high pressure rubber hose to connect the cutter with the pump. It permits the shear to reach a maximum pressure of 700 bar.


Art.no. **3137B**

Same as art.no. 3137P, but battery-powered.

new



Art. no.	Compression ratio	Supply	Tank capacity	Weight	Dimensions (LxWxH) (mm)
3137P	100:1	7 bar	5 l	60 kg	600x600x1200
3137B	-	12 Vcc	-		



new

Art.no. **3142**

Tyre-dismantling unit, equipped with a hydraulic gear pump for the safe and accurate separation of the tyre from the rim. With high-strength, transparent Lexan protection. The unit includes a manual control panel, a safety stop switch and a 10 m - electric cable with three-phase plug and earth cable.



Art. no.	Pressure	Max wheel diameter.	Work cycle down	Work cycle up	Power	Dimensions (LxWxH) (mm)
3142	10 t	20"	13 s	8 s	4 kW	750x1150x2310

