





## Art.no. 2214/50

Wall bracket in galvanized steel, suitable for the installation of pneumatic oil pumps, series "Power Bull", art. nos. 2055 – 2056. Dimensions: 290 x 290 x 250 mm – ø cylinder 50 mm. Distances between fixation holes: 230 x 205 mm.

# Art.no. 2214/55

Wall bracket in galvanized steel, suitable for the installation of pneumatic oil pumps, series "Power Bull", art. no. 2092. Dimensions: 290 x 290 x 250 mm - ø cylinder 55 mm. Distances between fixation holes: 230 x 205 mm.

## Art.no. 2214/80

Wall bracket in galvanized steel, suitable for the installation of pneumatic oil pumps, series "Power Bull", art. nos. 2093 - 2094 - 2096 - 2097 - 2097/DE. Dimensions: 290 x 290 x 250 mm – ø cylinder 80 mm. Distances between fixation holes: 230 x 205 mm.

# Art.no. 2214/110

Wall bracket in galvanized steel, suitable for the installation of pneumatic oil pumps, series "Power Bull", art. no. 2098. Dimensions: 290 x 290 x 250 mm – ø cylinder 110 mm. Distances between fixation holes: 230 x 205 mm.

Metal rack for wall mounting of pumps, length 1350 mm.







Art.no. 8534

Suction tube in galvanized steel, ø 55 mm, length 950 mm, with 90° - curved connection 1 1/4" BSP (M), with foot valve and metal bung adapter. Suitable for the use of wallmounted pneumatic oil pumps, series "Power Bull", with 208 I - drums.

# Art.no. 2216/1000

Suction tube in galvanized steel, ø 55 mm, length 1300 mm, with 90° - curved connection 1 1/4" BSP (M), with foot valve and metal bung adapter. Suitable for the use of wallmounted pneumatic oil pumps, series "Power Bull", with 1000 I - IBC -tanks.

## Art.no. 2218

Rubber suction hose SAE 100 R1 AT, ø 1 1/4", connections 1 1/4" BSP (F-F), length 1500 mm.

Suction tubes and suction hoses in other lengths available on demand!

#### Art.no. 4343/50

Metal bung adapter for the fixation of pumps, series "Power Bull", on drums or tanks. Connection 2" BSP (M) x 50 mm. Suitable for art. nos. 2057 – 2058.

## Art.no. 4343/55

Metal bung adapter for the fixation of pumps, series "Power Bull", on drums or tanks. Connection 2" BSP (M) x 55 mm. Suitable for art. nos. 2088 – 2091.





Art.no. 7150/12

Compressed air treatment unit, composed of pressure regulator with manometer and air filter with moisture separator (art. no. 7180/12) or pressure regulator with manometer, air filter with moisture separator and lubricator (art. no. 7150/12):

- Connections 1/2" BSP.
- Pressure range 0 8 bar.
- Filtration capacity of 20 microns.
- Moisture collection capacity 100 cc.
- Compressed air supply: 2880 NI/min.