

Kit 2984

Stationary pneumatic oil dispensing kit, for 208 l – drums, consisting of:



- Pneumatic double acting 3:1 - oil pump, art. no. 2020 (see page 41!);
- Plastic bung adapter for the fixation of pumps on drums, art. no. 4340;
- Open hose reel, adjustable arms series, art. no. 9090;
- 15 m – rubber hose Ø 1/2", art. no. 28715;
- 2 m – rubber connection hose Ø 1/2", art. no. 28702;
- Electronic flow meter for oil, with control gun, rubber protection guard, trigger guard, rigid outlet, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M), art. no. 2426 (see page 64!);
- Pressure regulator and air filter with moisture separator, art. no. 7180.

OPTIONAL

- Wall mounted gun holder with drip tray, art. no. 9784;
- Pivoting wall bracket for hose reel, art. no. 9767 (only suitable for single installations);
- Hydraulic spring brake device for the controlled and safe rewinding of hoses. Please add suffix "/HB" to the individual hose reel article number!



Art.no. **9784**
Wall mounted gun holder with drip tray.

MID MI-005
Approved

Kit 2984MID

Stationary pneumatic oil dispensing kit, for 208 l – drums, **approved for fiscal transactions** according to the European Directive 2014/32/EU, better known as **Measurement Instrument Directive MID MI-005**, consisting of:



- Pneumatic double acting 3:1 - oil pump, art. no. 2032 (see page 41!);
- Wall bracket in painted steel, for the fixation of the pump;
- Suction tube in galvanized steel, Ø 40 mm, length 950 mm, with 90° - curved connection 1" BSP (M), with foot valve, at. no. 2204, and bung adapter 2" BSP (M) x 40 mm, art. no. 4340, suitable for the use in 208 l – drums;
- 1.5 m - rubber suction hose 1", connections 1" BSP (F-F), art. no. 2205;
- Air separator kit, art. no. 2050, patented, **approved according to OIML R117-1** (see page 51!);
- Manometer for outlet pressure control;
- Open hose reel, adjustable arms series, art. no. 9090;
- 15 m – rubber hose Ø 1/2", art. no. 28715;
- 2 m – rubber connection hose Ø 1/2", art. no. 28702;
- Electronic oval gears flow meter for oil, approved for fiscal transactions according to **MID MI-005, Directive 2014/32/EU**, with control gun, rubber protection guard, trigger guard, oil flow control tube with transparent insert, flexible rubber outlet, Ø 1/2", with curved rigid 90° stem, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M), art. no. 2545 (see page 65!);
- Pressure regulator, air filter with moisture separator and lubricator, art. no. 7150;
- Wall mounted gun holder with drip tray, art. no. 9784;
- Pressure regulator, air filter with moisture separator and lubricator, art. no. 7150.

The configuration of components in this kit meets with all metrological standards and requirements concerning accuracy defined in the **Directive MID MI-005** and can be used therefore as approved system also in fiscal transactions.

OPTIONAL

- Pivoting wall bracket for hose reel, art. no. 9767 (only suitable for single installations);
- Hydraulic spring brake device for the controlled and safe rewinding of hoses. Please add suffix "/HB" to the individual hose reel article number!