

Electric pumps for the supply of fluids with particular chemical characteristics. It is recommended to check the compatibility of the fluid with the materials of the wetted pump components before use.

Art.no **6123**




Electric, selfpriming gear pump for the transfer of various fluids and chemical products; guarantees a constant flow and a low noise level.

Pump body and gears in IXEF.

Protection category IP 55.

Includes ON/OFF – switch and 1.5 m – cable with plug.

| Art. no. | Voltage | Current drain | Rpm | Power | Outlet pressure | Delivery | Connection threads | Weight | Dimensions (LxWxH) (mm) |
|-------------|------------------|---------------|------|-------|-----------------|----------|--------------------|--------|-------------------------|
| 6123 | 230 VAC 50 Hz | 5.3 | 1360 | 250 W | 2 bar | 25 l/min | 1/2" BSP (M) | 7 kg | 240x290x180 |



Art.no **6132**




Electric, selfpriming gear pump for the transfer of various fluids and chemical products; guarantees a constant flow and a low noise level.

Pump body in stainless steel AISI 304, gears in Kevlar®.

Protection category IP 55.

Includes ON/OFF – switch and 1.5 m – cable with plug and a bypass valve preset on 5 bar pressure.

| Art. no. | Voltage | Current drain | Rpm | Power | Outlet pressure | Delivery | Connection threads | Weight | Dimensions (LxWxH) (mm) |
|-------------|------------------|---------------|------|-------|-----------------|----------|--------------------|--------|-------------------------|
| 6132 | 230 VAC 50 Hz | 5.3 | 2650 | 370 W | 4 bar | 11 l/min | 3/8" BSP (F) | 7.5 Kg | 150x300x190 |



Art.no **6446**



Electric, centrifugal pump for the transfer of clean water.

Pump body and rotor in stainless steel AISI 304.

| Art. no. | Voltage | Current drain | Power | Outlet pressure | Delivery | Connection threads | Weight | Dimensions (LxWxH) (mm) |
|-------------|------------------|---------------|-------|-----------------|-----------|--------------------|--------|-------------------------|
| 6446 | 230 VAC 50 Hz | 5 A | 750 W | 4 bar | 160 l/min | 1 1/4" BSP (F) | 11 kg | 296x206x186 |

