

**Complete pneumatic grease supply kit, suitable for any kind of inside or outside use.  
Max pressure achievable: 400 bar.**

Grease



Art.no. **4922**

Portable and mobile pneumatic grease supply kit with 16 kg – steel pail, consisting of:


- Pneumatic grease pump, art. no. 4020;
- Pressure regulator, art. no. 7200;
- 3 m – high pressure hose SAE 100 R2 AT, 1/4", art. no. 4503;
- High pressure grease control gun, with 300 mm – steel braid outlet hose ø ext. 10 mm and 4 - jaws - hydraulic coupler, art. no. 4205;
- High pressure Z – swivel, art. no. 4221;
- Follower plate ø 230 mm;
- Steel pail with 2 wheels and carrying handle.



Art.no. **4925**

Portable and mobile pneumatic grease supply kit such as art. no. 4922, but with 5 kg - steel pail.

Art. no.	Max outlet pressure	Delivery	Connection compressed air	Compressed air supply	Weight	Dimensions (LxWxH) (mm)
<b>4922</b>	400 bar	2400 g/min	1/4" BSP (F)	2-8 bar	11 kg	240x390x930
<b>4925</b>	400 bar	2400 g/min	1/4" BSP (F)	2-8 bar	10 kg	240x390x890



Art.no. **4921**

Portable pneumatic grease supply kit for 18/25 kg - pails, consisting of:

- Pneumatic grease pump, art. no. 4020;
- Pressure regulator, art. no. 7200;
- 3 m – high pressure hose SAE 100 R2 AT, 1/4", art. no. 4503;
- High pressure grease control gun, 300 mm – steel braid outlet hose ø ext. 10 mm and 4 jaws - hydraulic coupler, art. no. 4205;
- High pressure Z – swivel, art.no. 4221;
- Follower plate, ø 310 - 260 mm, art. no. 4314\*;
- Metal drum cover, ø 330 – 290 mm, art. no. 4302\*.

\*See accessories on page 36 for pails/drums in different dimensions!



Art. no.	Max outlet pressure	Delivery	Connection compressed air	Compressed air supply	Weight	Dimensions (LxWxH) (mm)
<b>4921</b>	400 bar	2400 g/min	1/4" BSP (F)	2-8 bar	11 kg	240x240x890

